

MX9

WHAT DOES "ULTRA-RUGGED" MEAN?
YOUR TEST IS AS GOOD AS OURS.



To earn the "ultra-rugged" designation, a device must test to an IP rating of 67, a 6-foot drop to concrete, and a 2,000 cycle 1-meter tumble test. But the true tests of the MX9 don't happen in a lab. The MX9 proves itself on the loading dock when workers use it as a hammer to repair a pallet; when the farmer trusts it as his sole connection to suppliers; and across a widening spectrum of demanding conditions.

What kind of test will you subject the MX9 to? Use the WWAN radio and GPS to stay connected from the most remote locations. Take the MX9CS in the cold, where the built-in heater not only withstands -30°C, but in-and-out freezer transitions. Or try the MX9HL for peace of mind in hazardous locations.

From the port to the wheat field. From the warehouse to the construction site. From our tests to yours. Put the MX9 through its paces today. Visit lxe.com/mx9 to see customer testimonials and a product tour.



ULTRA-RUGGED
IP 67 rated, 6' drop to concrete, 2K 1m tumble test

GOES ANYWHERE
With WWAN radio and GPS options

CUSTOMIZABLE
Fully mappable keyboard with 10 one-touch function keys



IP 67



OUTDOOR DISPLAY



6ft



-30°C



GPS



VOICE READY



WWAN RADIO

MX9

TECHNICAL SPECIFICATIONS



PLATFORM

Processing & Memory

- PXA320, 800MHz
- 128MB SDRAM
- 128MB Flash
- SD expansion card to 4GB

System

- Windows® CE 5.0 Professional
- Non-volatile storage of resident drivers, applications & settings

Display & Touch Screen

- 3.7" (94 mm) color QVGA
- Outdoor readable, transfective
- Resistive touchscreen with stylus

Power Supply

- Full shift battery life with typical usage (CS units temperature-dependent)
- Fast recovery backup power for data retention
- Main battery low warning
- Active power management (configurable)

Enclosure

- Weight: 2.1 lbs. (34 oz.) with scanner, 802.11, Bluetooth and handstrap
- Dimensions: 9.9"x3.9"x2.7" (251mm x 99mm x 69mm)
- User replaceable battery
- Rubber overmold

ENVIRONMENTAL

- Operating temperature: -4° to +122°F (-20° to +50°C)
- Operating temp (CS Units): -22° to +122°F (-30° to +50°C) w/ heaters
- Storage temperature: -4° to +158°F (-20° to +70°C)
- Humidity: 5 to 95% non-condensing
- Drop: 6 ft. (1829 mm) to concrete
- Tumble: 2,000, 1m tumble test
- IP Rating: IP67
- MIL STD 810F

Approvals

- Hazardous Locations (HL units): Class I, Div-2, Groups ABCD with NRTL mark ISA 12.12.01, CSA C22.2#213
- Emissions: (EMI) FCC Part 15, Subpart B, Class A; EN 55022, Class A (CISPR 22)
- Immunity: (EMC)

EN 55024:1998

- Safety: UL 60950-1, CSA C22.2 No. 60950-1, EN 60950, IEC 60950
- Laser Safety: 21 CFR 1040.10, IEC 60825-1
- Battery Safety: UL 2054, IEEE 1725
- Hazardous Locations: Class 1, Div-2, Groups ABCD with NRTL mark ISA 12.12.01, CSA C22.2#213
- Radio: FCC Part 15 subpart C, IC RSS210, 102, EN 300 328, China SRRRC, Singapore IDA, Malaysia SIRIM
- Radio Safety: FCC O.E.T. Bulletin 65 Industry Canada RSS 102, EN 50360

CONNECTIVITY

Optional Software

- Wavelink® TE
- RFTerm® (TN5250, TN3270, VT220)
- Applock utility controls user application access & unwanted configuration changes
- Multiple localized languages
- Wavelink Avalanche and LXE eXpress Config

Interfaces

- USB Host & Client
- Powered RS-232
- Ethernet

- In-terminal charging
- Microphone
- Speaker with adjustable volume control
- Large scan status LEDs & power status LEDs

Radio Support

- 802.11 b/g
- 802.11 a/b/g
- Internal diversity antenna
- Bluetooth® 2.0 + EDR
- WPA or WPA2 security
- WWAN, GSM/GPRS
- GPS receiver
- Cisco® CCXv4 certified

ACCESSORIES

- Trigger handle
- USB and RS-232 adapter cables
- Desktop cradle with spare battery charging, USB client, USB host, & RS-232
- Active vehicle cradle
- 4-slot battery charger

- Vehicle power port adapter
- Carry case for MX9 w/ handle
- Carry case for MX9 without handle
- Holster for MX9 w/ handle

Download accessory catalog at lxe.com

DATA CAPTURE

Bar Code

- Standard range laser
- All-range laser (4 in. - 40 ft.) (102mm - 12m)
- 2D Imager
- Successful scan vibration signal

- Easy view scan LEDs
- Full symbology support
- Image capture, VGA



125 Technology Parkway
Norcross, GA 30092
1-800-664-4593
www.lxe.com